

## ⚠ WARNINGS AND CAUTIONS

**Important: ALWAYS** be sure to disconnect power before re-lamping or wiring the fixture. Read these instructions completely before starting installation.

To avoid the risk of fire and/or shock fixture must be installed in compliance to national and local electrical and building codes.

If an existing fixture is being replaced take special notice of which wires were connected in the outlet box.

**DO NOT SEPARATE ANY WIRES THAT MAY BE EXISTING IN THE JUNCTION BOX**  
**DO NOT DAMAGE THE INSULATION OF JUNCTION BOX WIRES.**

In Regular circumstances the BLACK wire will be "live", WHITE will be "neutral" and GREEN or BARE COPPER will be "ground". In older buildings it is always good practice to reconfirm the polarity of the wiring.

## NOTICE

- The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.

## ASSEMBLY INSTRUCTIONS

### Step 1

Remove fixture from its box, but do not remove protective paper.

### Step 2

Remove magnetic cover (2a) to separate mounting plate (1c) from fixture (3a) by removing fixture screws (2b).

**Important: This fixture must be mounted independently from junction box (1a), additional means of support is required.**

### Step 3

Attach safety hooks (4b) onto mounting plate (1c).

### Step 4

Make proper electrical connections (**black** to hot "L", **white** to neutral "N", **ground** to "GND") with wire nuts (1b) provided in hardware package and place driver (4a) inside fixture (3a).

### Step 5

Attach fixture (3a) to mounting plate (1c) with fixture screws (2b) and attach magnetic cover (2a).

### Step 6

Remove protective paper.

You are now ready to enjoy your fixture.

