TECHNICAL SUPPORT

1.855.855.8926 technicalsupport@aloralighting.com

A WARNINGS AND CAUTIONS

· Make sure POWER is COMPLETELY OFF at the fuse box

· Have your fixture installed by a qualified licensed electrician · 120V input

Please Note:

- · Prepare everything in a clear area
- \cdot Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- · Keep this installation sheet for future reference

NOTICE

- The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.
- This fixture is designed to be mounted on a correctly installed standard round or octagon box OR through a wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used, directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.

ASSEMBLY INSTRUCTIONS

Step 1

Remove fixture from its original package

Step 2

Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b)

Step 3

Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package

Step 4

Secure mounting plate (1c) to mounting surface with anchors (1f) and screws (1g) $\,$

Step 5

Secure your choice of rod (2d) (See Illustration 1) to canopy (2a) and fixture (3a), after feeding fixture wires through rod.

Step 6

Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package


Step 7


Attach canopy (2a) to mounting plate (1c) with canopy screws (2b)

Step 8

Install the recommended lamp (3b) (not provided) (referred on the socket label for maximum wattage and type) to fixture socket. Secure shade (3c) to lamp holder (3d) by threading clockwise.

You are now ready to enjoy your fixture.







P. 1.855.855.8926

CANADA: 19054 28th Ave., - Surrey, BC V3Z 6M3

USA: 3035 E. Lone Mountain Rd. - Las Vegas, NV 89081

www.aloramood.com

20220101